


Sensor Module-IAGO3

Ozone Sensor Module



HIGHLIGHT FEATURES

- High Precision TVOC Detection
- Fast Response and Recovery Time
- Low Power Consumption (<100mW) with High Efficiency
- Wide Operating Range : -10°C to 50°C and 15% to 90% Humidity
- Seamless Integration via I²C Communication Protocol, Plug-and-play Support
- Durable and Maintenance-free Operation

SPECIFICATIONS


Model Name	IAGO3
Detection	Ozone (O3)
Principle	Electrochemical
Measurement Range (ppm)	0 ~ 5
Resolution (ppm)	0.01
Accuracy (ppm)	±0.1±10% of Reading
Response Time (T90) (sec)	<60
Operation Temperature (°C)	-10 ~ 50 (Ta)
Operation Humidity (%RH)	15 ~ 90
Expected Operating Life	3 Years
Power Supply (V)	3.1 ~ 3.5
Power Consumption (mW)	<100
Interface	I ² C
Dimension (L x W x H/mm)	21 x 32 x 8

ORDER INFO.


P/N	Description
EA3-2AASMM80I12S3	IAGO3 O3 Sensor Module

MECHANICAL DRAWING


Slide View




Top View



Bottom View



APPLICABLE SENSOR MODULE LIST



CN2 1 x 4 Pin Header	
Pin	Signal
1	GND
2	NC
3	NC
4	NC

CN3 1 x 5 Pin Header	
Pin	Signal
1	VDD
2	SDA
3	SCL
4	GND
5	RSTn

HQ (Taiwan) T +886-2-7703-3000 / E sales@innodisk.com
CN T +86-755-2167-3689 / E sales_cn@innodisk.com
US T +1-510-770-9421 / E usasales@innodisk.com

EU T +31-40-3045-400 / E eusales@innodisk.com
JP T +81-3-6667-0161 / E jp_sales@innodisk.com

