



M.2 (P30) 4IE3

HIGHLIGHT FEATURES


- PCIe Gen 4 x4, NVMe 1.4
- Stable sustained performance
- LDPC ECC engine supported
- 256 bit AES hardware based encryption
- Hybrid write mode with SLC cache enable
- Dynamic Thermal Management

SPECIFICATIONS


Model Name	M.2 (P30) 4IE3
Flash Type	iSLC (3D TLC)
Interface	PCIe Gen 4 x4
Form Factor	M.2 2230 M Key
Capacity	40GB ~ 160GB
Sequential R / W (MB/sec, max.)	1,800 / 1,450
P/E Cycle	100,000
TBW (Max.)	1,978
Storage Temperature	-40°C ~ 85°C
Max. Power Consumption	3.3W
Max. Channels	8
External DRAM Buffer	N
H/W Write Protect	N
S.M.A.R.T.	Y
AES	Y (Optional)
TCG Opal	Y (Optional)
Dimension (W x L x H/mm)	Pure M.2 : 22.0 x 30.0 x 3.5 W/T with heat sink : 25.0 x 30.0 x 15.0
Vibration	20G@[7 ~ 2000Hz]
Shock	1500G@0.5ms
MTBF	>3 million hours
Warranty	5 Years

DIAGRAM

ST



WT



ORDER INFO.

Operating Temperature	Standard Grade (0°C ~ 70°C)	Industrial Grade (-40°C ~ 85°C)
40GB	DHM23-40GDH1KCBDF	DHM23-40GDH1KWBDFFH
80GB	DHM23-80GDH1KCBDF	DHM23-80GDH1KWBDFFH
160GB	DHM23-A60DH1KCBDF	DHM23-A60DH1KWBDFFH

For TCG Opal function, the PN Code 10th ~ 12th will be DH2.

HQ (Taiwan) T +886-2-7703-3000 / E sales@innodisk.com

CN T +86-755-2167-3689 / E sales_cn@innodisk.com

US T +1-510-770-9301 / E usasales@innodisk.com

EU T +31-40-3045-400 / E eusales@innodisk.com

JP T +81-3-6667-0161 / E jp_sales@innodisk.com

innodisk